

Index

A

AC-DC rectification, 124
acceleration profiles, 121
active diodes, 118
active eEHs, 128
active full-wave (AFW)
 rectifier, 126
aging, 31
all-fire event detection circuitry, 120
all-fire event, 121
all-fire voltage level, 121
aluminum nitride (AlN), 20
amorphous metallic glass
 Metglas, 28

B

back electromotive force, 112
bandwidth of vibration-based
 energy-harvesting devices, 83
barium titanate, 12
Beam-vibration-mode, 16
bidirectional flyback
 converter, 131
bidirectional transistors, 131
bismuth sodium titanate, 19
bistable, 80
BNT, 19
broadband excitation, 118
buffer circuit, 113, 116

C

cantilever vibrating beam, 60
cantilevered beam, 59

cantilevered type, 66
cantilevered vibration harvesting
 generator, 147
capacitive loads, 109–110
CC circuit, 140
ceramic composites, 17
charge balance, 12
charge-collecting electrodes, 14
charge-constrained cycle, 130
charge-constrained mode, 23
charge/discharge phases, 129
charge–voltage diagrams, 130
charging voltage, 116
collection and conditioning (CC)
 circuit, 102
collection and storage
 circuit, 124
collection circuit, 109
collection circuits, 106, 111
collection process, 109
compliance coefficient, 14
compliance coefficients, 16
composite structures, 17
compression, 120
compressive loading, 120
compressive preloading, 66
conditioning circuit, 113
constant-voltage-cycle conditioning
 circuit, 130
constitutive equations of
 piezoelectric materials, 13
continuous and narrowband, 140
continuous oscillatory motions, 63

- continuous periodic multiple-harmonic oscillatory motion, 63
- continuous periodic simple harmonic oscillatory motions, 63
- continuous random oscillatory motions, 63
- continuous rotation, 58
- cross-coupled transistor rectifier, 126
- Curie temperature, 19
- Curie temperatures, 18
- D**
- damping, 54
- DC voltage multiplication, 132
- DC-DC boost circuit, 124
- DC-DC charge pumps, 127
- DC-to-DC buck–boost, 113
- DC-to-DC converter, 105
- DC-to-DC regulator, 114
- delayed-switching, 120
- depolarization, 12
- depoling, 31
- detection, 150
- dielectric permittivity, 14–15
- dipole polarization, 26
- domain walls, 12
- double synchronized switch harvesting, 119
- Dynamos, 138
- E**
- effective mass, 82
- effective stiffness, 82
- effective volume of piezoelectric material, 113
- efficiency, 65
- efficient operation, 113
- elastic deformation, 54
- electret, 26, 127, 145
- electret-based design, 127
- electret-based devices, 129
- electret-based eEHs, 126
- electret-based electrostatic transducer, 145
- electret-based electrostatic transducers, 26
- electret-free design, 127
- electric displacement (flux density), 14
- electric field component, 14
- electrical energy upon target impact, 147
- electrical generators, 52
- electrical potential energy, 16, 106
- electromagnetic and magnetostrictive transducers, 106
- electromagnetic energy harvester, 132
- electromagnetic energy, 4
- electromagnetic induction generator, 21
- electromagnetic induction, 124
- electromagnetic transducer, 145
- electromagnetic transducers, 88, 125
- electromagnetic transduction, 138, 141
- electromechanical coupling, 17
- electromechanical figure of merit, 113, 117
- electromechanical figures of merit, 119
- electromotive force, 20, 124
- electronic switching devices, 129
- electrostatic energy harvesters, 145
- electrostatic field, 112
- electrostatic forces, 61
- electrostatic transducer, 127
- electrostatic transducers, 23, 127
- electret-based eEHs, 127
- electret-based energy harvesters, 127
- electret-based harvesters, 127
- electret-free eEHs, 129

electromagnetic, 30
electromagnetic generator, 20
electromagnetic induction
 transducers, 20
electronic loads, 102
electrostatic, 30
electrostatic energy harvesters, 126
electrostatic transducers, 23, 26
emergency-event-detection and
 warning systems, 146
energy demands, 140
energy transfer, 119
energy transfer time, 109
energy-harvesting cycle, 108, 131
energy-harvesting device, 54, 149
energy-harvesting devices, 120
energy-harvesting process, 109
equation of motion, 68
event detection, 120, 122
event detection circuit, 124
event-detection sensors, 120
event-driven alerts, 146
extremum values, 119
extremum voltage points, 113

F

fatigue failure, 31
ferroelectric ceramic, 12
fibrous composites, 17
figure of merit, 119
firing accelerations, 148
flux-shaping method, 125
flyback capacitor, 129
flyback conditioning circuits, 128
flyback transformer, 105, 113, 116
flywheel, 58
force, 109
forcing function, 69
four-diode bridge rectifier, 114
frequency-doubling interfacing
 mechanism, 76
friction, 54
full wave rectifier, 118

G

generated charges, 109
gravitational field, 54
GravityLight, 52
gun-fired in munitions, 140
gun-fired munitions, 120, 140,
 147–148

H

half-wave rectifier, 118
harvested energy, 109
hard PZT, 12
high-G-hardened piezoelectric-
 based energy-harvesting power
 sources, 150
High-frequency oscillatory
 motions, 63
high-temperature stability, 19
host system, 7, 52, 140, 143
host, 52
human activity, 4
human locomotion, 5

I

ICs for collection and
 conditioning, 142
IEEE Standard, 13
impact, 84
impact-event-detection sensors, 147
impact-generating stops, 78
impact-type loading, 120
implanted charge stability, 26
impulse events, 57
impulsive loading, 84, 92
in-parallel design, 61
in-series design, 61
induced emf, 124
inductive switching, 118
inductor switching, 114
initiation and switching, 120
initiator circuitry, 152
integrated system, 55
interacting magnets, 79

interfacing mechanism, 7, 52, 74
interfacing mechanisms, 57, 140
interfacing methods, 54
intermittent engagement, 78
internal damping, 19, 54, 78, 150
inverse magnetostrictive, 28
inverse piezoelectric effect, 10

K

kinematic nonlinearity, 74, 78
kinetic energy, 7, 52, 55

L

lead zirconate titanate (PZT), 12
lead-free materials, 18
leakage, 122
living joints, 78
load, 109
low-frequency, 67
low-power circuitry, 152
“Low-frequency” continuous
oscillatory motions, 63

M

magnetic circuit, 129
magnetic field, 22
magnetic flux, 20
magnetic force (magnetic
drag), 22
magnetically induced current, 125
magnetoelastic, 28
magnetomechanical, 28
magnetostrictive, 30
magnetostrictive energy
harvester, 132
magnetostrictive-material-based
transducers, 28
mass–spring element, 147, 150
mass–spring interfacing, 148
mass–spring system, 52, 86
matching network, 104
maximum energy collection, 109
maximum power transfer, 116

mechanical energy from in-flight
vibration and oscillatory
motions, 147
mechanical energy, 7
mechanical energy to be
harvested, 140
mechanical potential energy, 16
mechanical resonator, 145
mechanical shocks and impacts, 117
mechanical stress, 15
mechanical-to-electrical energy
conversion, 107
MEMS, 145
MEMS-based devices, 118, 127
MEMS-based vibrational energy
harvesting, 146
micro-electromagnetic energy
harvesters, 124
micro-energy harvesters, 122
micro-generators, 21, 124
mistuning, 120
mode, 14
modes of vibration, 59
monocrystal, 11
MOSFET switch, 116
motion constraints, 69, 78
motion-doubling linkage
mechanisms, 74
munitions firing, 120

N

narrowband frequency
spectrum, 117
natural frequency, 52, 82
no-fire conditions, 121
no-fire events, 121
nonlinear behavior, 57
nonlinear kinematics, 69
nonresonant applied strain, 116

O

one-shot energy-harvesting power
sources, 84

one-shot harvesting, 122
one-shot piezoelectric generators, 120
one-shot power sources, 120
open-circuit, 116
open-circuit voltage, 14, 107
operational life, 30
oscillatory motion frequency-
increasing, 70
oscillatory motion, 56

P

passive circuit, 122
passive circuitry, 152
pendulum-type mechanism, 73
performance degradation, 31
periodic oscillatory motion, 66–67
periodic oscillatory motions, 56
permanent magnet, 20
perovskite ferroelectric, 19
photovoltaic devices, 4
piezoelectric, 30
piezoelectric and electrostatic
harvesters, 106
piezoelectric-based, 151
piezoelectric-based energy
harvesters, 148
piezoelectric capacitance, 109
piezoelectric ceramics, 17
piezoelectric constant, 14–15
piezoelectric creep, 31
piezoelectric effect, 10, 12
piezoelectric element, 114
piezoelectric–magnetostrictive
composites, 29
piezoelectric polymers, 17
piezoelectric stack, 150
piezoelectric transducer, 107,
120, 147
piezoelectric transducers, 10, 58, 106
piezoelectric voltage, 116, 119
piezoelectricity, 10, 13
PMN-PT, 17
PMNT, 17

polar axis, 11
polarity reversal, 111
polarization, 12
polarized, 12
poled piezoelectric, 10
polycrystalline PZT-5A, 17
polycrystals, 11
polyvinylidene fluoride, 17
potential electrical energy, 15
potential energy to electrical
energy, 58
potential energy, 7, 52, 54, 55
power harvested, 119
progressive degradation, 31
pulsed loading, 120
pulsed operation, 117
push-button piezoelectric
igniters, 138
PZN-PT single crystals, 17
PZNT, 17
PZT–polymer composites, 20
PZT, 17
PZT-5H ceramics, 17

Q

quartz, 12
quasi-permanent electric charge, 26

R

random input forcing functions, 83
rectifier diode bridge, 105
rectifying circuitry, 106
regenerative braking system, 138
regenerative braking, 52
relaxor-based single crystals, 17
relaxor-PT crystals, 18
remote sensing, 145
resistive load, 111
resonance, 64
resonance condition, 119
resonant structures, 117
reverse saturation current, 126
Rochelle salt, 12

rotary or linear kinetic energy, 124
rotary-type electromagnetic transducers, 58
rotating electromagnetic transducers, 126

S

safety and all-fire detection circuitry, 151–152
safety and event-detection circuitry, 154
Schottky diodes, 132
secondary vibrating elements, 59, 72
self-powered, 150
self-powered conditioning circuits, 120
self-powered electrical initiation, 147
self-powered event-detection sensor, 153–154
self-powered event-detection sensors, 138
self-powered shock-loading event detection, 140
self-powered wireless sensor, 145
self-start feature, 126
series SSHI, 115
shelf life, 30
shock loading, 84, 153
shock-loading event, 122, 150
shock-loading event detection logic, 120
shock-loading-event detection sensor, 151
shock-loading-event-detection switching device, 153
short-duration impulse, 56
short-duration pulsed loading, 124
silicon-dioxide-based electrets, 27
single-crystal PMN-PZT, 17
sinusoidal strain, 107
sinusoidal strain profile, 113
smoothing capacitor, 114

soft PZT, 12
solar energy, 4
solar harvester, 143
split-capacitor rectification, 125
SSHI-MR collection circuit, 118
standard AC-to-DC circuit, 113
standard circuit, 117
standard circuit design, 104
standard energy-harvesting circuit, 105
step-down buck converters, 128
stiffness, 15
storage capacitor, 124
strain, 14–15, 58
stress, 14
switch inductor, 114
switched inductive element, 112
switched-mode operation, 126
synchronization, 120
synchronized energy exchange, 114
synchronized switch harvesting on inductor, 114
synchronized switch harvesting, 117
synchronous electric charge extraction, 116
synchronous electric-charge extraction (SECE), 105
synchronous magnetic flux extraction, 124
synchronous-switched-for-harvesting (SSH) technique, 105

T

tank circuit, 114, 123
Teflon, 26
Terfenol-D, 28
textured piezoelectric, 20
thermal effects, 31
thermoelectric effect, 3
tire-pressure-monitoring, 140
tire pressure monitoring systems, 143
tourmaline, 12
transducer, 7

- transducers, 52
 - tristable, 80
 - two-stage device, 74
 - two-stage interfacing mechanism, 62, 70, 89
 - two-stage interfacing mechanisms, 59, 71, 73
- U**
- unloaded open-circuit voltage, 108
 - unloaded voltage/strain response, 108
- V**
- variable-capacitance capacitor, 25
 - vibration energy harvesters, 140
 - vibration energy-harvesting power sources, 140
 - vibration-based energy-harvesting device, 66, 82
 - vibration-based harvesters, 65
 - vibration-based sources of mechanical energy, 125
 - vibration-based types, 88
 - vibratory mass and spring element, 142
 - Villari effects, 28
 - voltage doublers/quadruplers, 124
 - voltage extremum, 111
 - voltage-constrained cycle, 130
 - voltage-constrained mode, 23, 25
- Z**
- zig-zag structure, 82



Dr. J. Rastegar received his B.S. from SMU in 1969 and his M.S. and Ph.D. Degrees from the Mechanical Engineering Department of Stanford University in 1972 and 1977. He then joined the General Engineering and Bioengineering faculty at the University of Illinois at Urbana-Champaign, and after several years of work in the industry, he joined the Mechanical Engineering Department at Stony Brook University in 1987. He has published over 240 journal and conference articles. He holds 194 issued and over 90 pending U. S. patents in the fields of sensors; actuation devices; medical systems and devices; safety and accident prevention devices; power sources and components; mechanical tools, devices, and structural elements; military products and components; and optical and electronic devices. He served as Associate Editor of ASME Journal of Mechanical Design and Journal of Medical Devices. He is a Fellow of the American Society of Mechanical Engineers (ASME) and recipient of its “2010 Machine Design Award” for “eminent achievements as an inventor and scholar in the field of machine design, particularly in the area of smart actuation and control.” He is a fellow of the National Academy of Inventors.



Dr. Harbans Dhadwal received his B.Sc. and Ph.D. degrees from the Electrical Engineering Department of Queen Mary College of the University of London in 1976 and 1980. He then took the position of Higher Science Officer at the Royal Aircraft Establishment in Farnborough, England. In 1982 he took a post-doctoral position in the Department of Chemistry at Stony Brook University, and in 1984 he joined the faculty in the Electrical and Computer Engineering Department. He has had visiting appointments at IBM Thomas Watson Research Center in New York and at the NASA Glen Research Center. He has published over 100 journal and conference articles, and holds 13 U.S. patents. His research has spanned multidisciplinary fields of electronics, polymer physics, and marine sciences through the use integrated fiber optics, optoelectronics, photon correlation spectroscopy, fluorescence spectroscopy, light scattering and RF sensor systems. He is a senior member of the Institute of Electrical and Electronics Engineers (IEEE), and a member of the Optical Society of America and SPIE.