

An image-based multi-directional reflectance measurement setup for flexible objects (Erratum)

Aditya S. Sole, Ivar Farup, Gjøvik University College, (Norway), Shoji Tominaga, Chiba University (Japan)

Proceedings Volume 9398, *Measuring, Modeling, and Reproducing Material Appearance 2015*; 93980J (2015) <https://doi.org/10.1117/12.2076592>

Event: [SPIE/IS&T Electronic Imaging](#), 2015, San Francisco, California, United States

Online Publication Date: 13 March 2015

Erratum Published: 6 August 2019

A revised version of this manuscript was published on 6 August 2019. Details of the revision are provided in the text that accompanies this Erratum. The original paper has been updated.

Revision:

Equation (4) on page 5 was originally written as below:

$$f_r(\theta_i, \phi_i, \theta_r, \phi_r) = \frac{dL_r(\theta_i, \phi_i, \theta_r, \phi_r, E_i)}{dE_i(\theta_i, \phi_r)} \quad (4)$$

It has been edited to read as follows:

$$f_r(\theta_i, \phi_i, \theta_r, \phi_r) = \frac{dL_r(\theta_i, \phi_i, \theta_r, \phi_r, E_i)}{dE_i(\theta_i, \phi_i)} \quad (4)$$